

**Frame mark (EU)**

U EN166 FT CE

Lens mark (EU)

2C-1.2 U 1 FT KN CE

Conditions of use

Standard brightness, Low brightness

Lens color

Clear

Frame technologyOverspec, Adjustment of temples in length,
Adjustment of temples in inclination**Lens technology**

Anti-Scratch (K), Anti-Fog (N)

Lens material

Polycarbonate

Standards

EN166, EN170

Scale number

(2C-1.2)

Mechanical resistance

Low energy impact (F)

Optical class

Optical class (1)

Optional requirements

Resistance to surface damage by fine particles (K), Resistance to fogging of oculars (N), Protection against high speed particles at extreme temperatures -5°/+55° C (T)

Weight

43g

>> <https://www.univetsafety.com/en/products/safety/spectacles/519/519-clear-2/>



01.

OVERMOULDED TERMINAL FOR
BETTER COMFORT AND STABILITY

02.

SIDE VENTING

03.

ADJUSTMENT OF TEMPLES IN
LENGTH AND INCLINATION

04.

CAN BE WORN OVER PRESCRIPTION
GLASSES

Attention! Any images on this page illustrate the frame technologies of the product family in question and may represent frame and lens colours that do not correspond to the product code of the following sheet.

HEADQUARTERS

Univet S.r.l. Via Giovanni Prati 87 25086 Rezzato - Telephone 030 2499411 - Fax 030 2499430 - info@univetsafety.com
VAT. IT02506570163