

# Safety / Spectacles / 5X9

# 5X9 - Clear 1

Code: 5X9.01.11.00 Date: 21-06-22 1/2

The two-lens structure of the model 5X9 permits to provide the device with alternative materials to polycarbonate lenses, offering protection to a greater number of professional fields. The integrated flip-up perfectly combines with the glasses forming a unique modular system for maximum flexibility of use, made possible by the wide range of filters in the catalogue.



Lens mark (EU)	Conditions of use
2C-1.2 U 1 FT K CE	Standard brightness, Low brightness
Frame technology	Lens technology
Adjustment of temples in length, Adjustment of temples in inclination, Rubber Terminal, Terminal tilting movement, SoftPad, Flip-up	Anti-Scratch (K)
Standards	Scale number
EN166, EN170	(20-1.2)
Optical class	Optional requirements
Optical class (1)	Resistance to surface damage by fine particles (K), Protection against high speed particles at extreme temperatures -5°/+55° C (T)
	Frame technology  Adjustment of temples in length, Adjustment of temples in inclination, Rubber Terminal, Terminal tilting movement, SoftPad, Flip-up  Standards  EN166, EN170  Optical class


## Weight

35g polycarbonate version, 41g CR39, 45g glass version



Safety / Spectacles / 5X9 2/2

>> https://www.univetsafety.com/en/products/safety/spectacles/5x9/5x9-clear-1/



01.

#### SIDE SHIELD WITH VENTILATION SYSTEM

Increases the level of peripheral protection while reducing the risk of fogging, thanks to a ventilation vent

## INCLINATION ADJUSTMENT

Allows to adjust the height of the glasses to ensure maximum optical quality

03.

#### RUBBER TERMINAL WITH TILTING MOVEMENT

Allows the glasses to adhere to the temples for a perfect grip

04.

#### LENGTH ADJUSTMENT

Allows to obtain the correct fit and work in constant safety

Attention! Any images on this page illustrate the frame technologies of the product family in question and may represent frame and lens colours that do not correspond to the product code of the following sheet.