

RIDUZIONE 241 - prosystemitalia.com

RIDUZIONE 241 - Gruppo 241Z



Impiego

Riduzione concentrica per tubi scanalati in acciaio.

Dati tecnici

Pressione di esercizio: 20 bar.

Materiale:

- Corpo: ghisa ASTM A536;
- Trattamento superficiale: zincato a caldo.

DN	D x d ["]	D x d [mm]	L [mm]
32 x 25	1" 1/4 x 1"	42,4 x 33,7	64
40 x 25	1" 1/2 x 1"	48,3 x 33,7	-
40 x 32	1" 1/2 x 1" 1/4	48,3 x 42,4	64
50 x 25	2" x 1"	60,3 x 33,7	64
50 x 32	2" x 1" 1/4	60,3 x 42,4	64
50x40	2" x 1" 1/2	60,3 x 48,3	64
65x32	2" 1/2 x 1" 1/4	76,1 x 42,4	64
65x40	2" 1/2 x 1" 1/2	76,1 x 48,3	64
65x50	2" 1/2 x 2"	76,1 x 60,3	64
80 x 32	3" x 1" 1/4	88,9 x 42,4	-
80 x 40	3" x 1" 1/2	88,9 x 48,3	-
80x50	3" x 2"	88,9 x 60,3	64
80x65	3" x 2" 1/2	88,9 x 76,1	64
100x50	4" x 2"	114,3 x 60,3	70
100x65	4" x 2" 1/2	114,3 x 76,1	70
100x80	4" x 3"	114,3 x 88,9	70
125x65	5" x 2" 1/2	139,7 x 76,1	74
125x80	5" x 3"	139,7 x 88,9	74
125x100	5" x 4"	139,7 x 114,3	74

150 x 50	6"X2"	168,3 x 60,3	-
150 x 65	6"X2"1/2	168,3 x 76,1	-
150X80	6"X3"	168,3 x 88,9	-
150X100	6"X4"	168,3 x 114,3	-
150X125	6"X5"	168,3 x 139,7	-
200X100	8"X4"	219,1 x 114,3	100
200X150	8"X6"	219,1 x 168,3	100
250X200	10"X8"	273,0 x 219,1	159
300x250	12"X10"	323,9 x 273,0	-

Certificazioni

FM, UL.



Tipo	Kg	Pezzi per confezione	Codice Articolo
60,3x 48,3 mm 2" x 1"½	0.56	75	241P060048Z
88,9x 60,3 mm 3" x 2"	0.8	45	241P089060Z
88,9x 76,1 mm 3" x 2"½	0.94	36	241P089076Z
114,3x 76,1 mm 4" x 2"½	1.28	27	241P114076Z
114,3x 88,9 mm 4" x 3"	1.45	27	241P114089Z
139,7x 76,1 mm 5" x 2"½	1.72	15	241139076Z
168,3x 60,3 mm 6" x 2"	2.27	12	241168060Z
168,3x 88,9 mm 6" x 3"	2.18	20	241P168089Z
168,3x114,3 mm 6" x 4"	2.39	20	241P168114Z
168,3x139,7 mm 6" x 5"	2.46	12	241P168139Z
219,1x168,3 mm 8" x 6"	4.53	10	241P219168Z
273,0x219,1 mm 10" x 8"	9.03	8	241P273219Z
329,3x273,0 mm 12" x 10"	0	1	241P324273Z