




SEMIRACCORDO SR.
WG. FERRULE
FERRULE SR.
ENLACE SR.


GUARNIZIONE
GASKET
JOINT
JUNTA

TAPPO
SOLID END CAP
BOUCHON
TAPÓN


K14 WI



K40 I



K16 I



DN	B	C	D	K	gr
1/8"	21,0	6,9	10,2	34,0	20
1/4"	21,0	10,2	13,7	34,0	20
3/8"	21,0	13,9	17,2	34,0	20
1/2"	21,0	18,0	21,3	34,0	40
3/4"	28,6	23,6	26,9	50,5	80
1"	28,6	30,4	33,7	50,5	75
1 1/4"	28,6	39,1	42,4	50,5	60
1 1/2"	28,6	45,0	48,3	64,0	95
2"	28,6	56,3	60,3	77,5	145
2 1/2"	28,6	72,1	76,1	91,0	150
3"	28,6	84,9	88,9	106,0	210
4"	28,6	110,3	114,3	130,0	270
5"	28,6	135,7	139,7	155,0	470
6"	28,6	163,3	168,3	183,0	555
8"	28,6	214,1	219,1	233,5	700


DN	A	B	C
1/8"	34,0	5,5	6,9
1/4"	34,0	5,5	10,2
3/8"	34,0	5,5	13,9
1/2"	34,0	5,5	18,0
3/4"	50,5	5,5	23,6
1"	50,5	5,5	30,4
1 1/4"	50,5	5,5	39,1
1 1/2"	64,0	5,5	45,0
2"	77,5	5,5	56,3
2 1/2"	91,0	5,5	72,1
3"	106,0	5,5	84,9
4"	130,0	5,5	110,3
5"	155,0	5,5	135,7
6"	183,0	5,5	163,3
8"	233,5	5,5	214,1

DN	B	K	gr
1/4"	6,4	34,0	15
3/8"	6,4	34,0	15
1/2"	6,4	34,0	70
3/4"	6,4	50,5	70
1"	6,4	50,5	70
1 1/4"	6,4	50,5	70
1 1/2"	6,4	64,0	140
2"	6,4	77,5	260
2 1/2"	6,4	91,0	350
3"	6,4	106,0	480
4"	6,4	130,0	750
5"	13,0	155,0	1.890
6"	13,0	183,0	2.600
8"	13,0	233,5	4.100


TEE EL.
TEE PE.
TE BL.
TE EL.

CURVA 90° ES.
BEND 90° WE.
COUDE 90° BS.
CODO 90° ES.

W7 I



W2C I



DN	A	B	C	D	gr
1/4"	25,5	51,0	10,2	13,7	30
3/8"	25,5	51,0	13,9	17,2	40
1/2"	25,5	51,0	18,0	21,3	50
3/4"	28,5	57,0	23,6	26,9	100
1"	38,0	76,0	30,4	33,7	150
1 1/4"	47,5	95,0	39,1	42,4	235
1 1/2"	57,0	114,0	45,0	48,3	350
2"	63,5	127,0	56,3	60,3	470
2 1/2"	76,0	152,0	72,1	76,1	750
3"	85,5	171,0	84,9	88,9	930
4"	105,0	210,0	110,3	114,3	1.460
5"	124,0	248,0	135,7	139,7	2.070
6"	150,0	300,0	163,3	168,3	3.080

DN	A	C	D	gr
1/4"	20,2	10,2	13,7	20
3/8"	28,5	13,9	17,2	25
1/2"	31,8	18,0	21,3	30
3/4"	28,6	23,6	26,9	45
1"	38,1	30,4	33,7	100
1 1/4"	47,6	39,1	42,4	150
1 1/2"	57,2	45,0	48,3	200
2"	76,2	56,3	60,3	340
2 1/2"	95,2	72,1	76,1	530
3"	114,3	84,9	88,9	820
4"	152,4	110,3	114,3	1.340
5"	190,5	135,7	139,7	2.020
6"	228,6	163,3	168,3	2.890