

Safety / Spectacles / 501

501 - Clear 2

Code: 501.00.00.11

Date: 21-06-22 1/2



Frame mark (EU)

U EN166 F CE

Lens mark (EU)

2-1.2 U 1 FN CE

Conditions of use

Standard brightness, Low brightness

Lens color

Clear

Frame technology

Nose pad set-up, Adjustment of temples in length, Adjustment of temples in inclination

Lens technology

Anti-Fog (N), Anti-Scratch

Lens material

Polycarbonate

Standards

EN166, EN170

Scale number

(2-1.2)

Mechanical resistance

Low energy impact (F)

Optical class

Optical class (1)

Optional requirements

Resistance to fogging of oculars (N)

Weight

34g polycarbonate version, 45g CR39

>> <https://www.univetsafety.com/en/products/safety/spectacles/501/501-clear-2/>



01.

SPECTACLE WITH WIDE COVERAGE
AREA AND PERFECT ADHERENCE TO
THE FACE

02.

MICROMETRIC ADJUSTMENT OF
TEMPLES LENGTH

03.

STEP-FREE ADJUSTMENT OF THE
FRONT ANGLE

04.

VENTED SIDE SHIELDS

05.

ADJUSTABLE NOSE PAD

Attention! Any images on this page illustrate the frame technologies of the product family in question and may represent frame and lens colours that do not correspond to the product code of the following sheet.

HEADQUARTERS

Univet S.r.l. Via Giovanni Prati 87 25086 Rezzato - Telephone 030 2499411 - Fax 030 2499430 - info@univetsafety.com
VAT. IT02506570163