FUSION+

A COMBINATION OF PERFORMANCE, SAFETY AND STYLE

Inspired by the best assets of its predecessors, FUSION+ brings fantastic optical performance and greater comfort to the range.

Suitable for all welding, FUSION+ is the very essence of innovation.



525 g

SUPPLIED WITH

- Variable shades filter 5-8 / 9-13
- Adjustable headband
- Screen guards

TYPE

• Electro-optical filter

SPARE PARTS AVAILABLE

- Inner and outer screen guards
- Adjustable headband
- Sweatband

- **LOW BATTERY SIGNAL & CHANGEABLE BATTERY**
- **+ VARIABLE SHADES 5-8/9-13**
- **#** REACTION TIME: 0.10 MS
- **UV AND IR PROTECTION**

- 4 INDEPENDENT SENSORS
- 100 X 53 MM FIELD OF VISION
- **+** TWO YEAR WARRANTY



A COMBINATION OF PERFORMANCE, SAFETY AND STYLE

MODEL	REFERENCES	DESCRIPTION	WEIGHT	NORMS
	FUSV	Electro-optical helmet with:		EN379/EN175
		B7VP Electro-optical filter with variable shades 5-8 / 9-13	525 g	EN379
		Adjustable headband		C€
FUSION+	B7VP	Electro-optical filter with variable shades 5-8 / 9-13	148 g	EN379
Variable Shade	COVFUSPEXT	115 x 104 mm outer screen guard	15 g	EN166
	COVFUSPINT	105 x 58 mm inner screen guard	15 g	EN166
	STFUSP	Adjustable headband	115 g	C€
	BESM	Sweatband	3 g	CE

NORMS

EN175, standard for helmets

EN175 is the European standard that specifies the requirements and test methods related to personal protective equipment used to protect the operator's eyes and face from harmful optical radiation and other specific risks due to regular welding or cutting processes or other associated techniques. The standard specifies protection, including ergonomic aspects, against various risks or hazards including radiation, fire, mechanical and electrical risks. This standard defines the terms used and specifies the requirements related to materials, design and manufacture.

EN379, standard for filters

The specifications of the standard apply if such a filter is used for continuous observationof the welding process and if it is only used during the period when the arc is struck.

Bollé Safety product approval certificates to CE standards will be sent on request.

Electro-optical filter B7VP			
DIMENSION	110 x 90 mm		
LENS THICKNESS	10 mm		
FIELD OF VISION	100 x 53 mm		
SENSORS	4		

Sensors				
SENSORS	4 independent photoelectric detectors			
POWER SUPPLY	solar energy + battery (CR2032)			
CLEAR STATE	Level DIN 4			
DARKENED STATE	Level DIN 5-8/9-13			
REACTION TIME	0.10 ms			

CHARACTERISTICS				
USES	Coated electrodes, MIG / MAG, TIG, PLASMA, grinding			
CONFORMS TO	EN379 / EN175 - UV et IR protection - permanent DIN16			
WARRANTY	2 years			

Markings B7VP

 ϵ 4/5-8 / 9-13 / **EN 379** Scale number of the Identification of the Optical Class Class number of Class number Class number Standard number European clear state / darkened manufacture the diffusion of of the variations of the angle state Bollé Safety the light in luminous dependence Symbol

Identification of the manufacturer Bollé Safety

EN 175 В

Markings for the helmet

Reference

equipment for

electric welding

Minimum Strenght standard about

European Community Symbol

 ϵ

PACKAGING AND EAN13 CODE						
FU	ısv	В7VР	COVFUSPEXT	COVFUSPINT	STFUSP	BESM
3660740005696 per unit	3660740205690 per 6	3660740005702 per unit	3660740006440 per 10	3660740006457 per 10	3660740006471 per 10	3660740004569 per 5

of luminous











Non-contractual pictures 31/08/2017

Europe Bollé Safety 95 rue Louis Guérin 69100 Villeurbanne - France Tél.: 00 33 (0) 4 78 85 23 64 Fax: 00 33 (0) 4 78 85 28 56 contact@bolle-safety.com

U.K. Bollé Safety Unit C83 - Barwell Business Park Leatherhead Road - Chessington Surrey - KT9 2NY

Tél.: 00 44 (0)208 391 4700 Fax: 00 44 (0)208 391 4733 e-mail: sales@bolle-safety.co.uk

transmittance class

