

DermaShield™

73-711

Disposable Beaded Neoprene Glove
for Aseptic Environments

NE

Neoprene

Durability and advanced allergy protection

- Latex and accelerator free to protect against Type I and reduce potential of Type IV allergies
- Offers chemical resistance to a broad spectrum of chemicals*
- Proprietary neoprene blend offers comfort and flexibility
- Allows easy donning and eliminates cuff roll down



Industries

- Medical/Research Laboratories
- Pharmaceutical
- Chemical Processing

Applications

- Biotechnologies
- Blending operations
- Cytostatics handling
- Filtration processes
- Handling active material
- Maintaining equipment & instruments
- Organic / material synthesis
- Preparing pharmaceutical products
- Protection from fluids
- Semiconductor manufacturing
- White goods assembly

TECHNICAL DATA SHEET:

PRODUCT INFORMATION:

Material	Polychloroprene (Neoprene)
Color	Green
Glove Design	Hand-specific, Powder Free, Smooth fingers
Cuff	Beaded with SUREFIT™ Technology
Sterilization	Gamma radiation, Sterility Assurance Level 10 ⁻⁶
Clean Room Compatibility	All packaging is printed with cleanroom-compatible IPA-resistant ink. The gloves are triple-bagged for superior contamination control.
Manufacturing/QMS Audit Standards	ISO 9001
Regulatory/Standards Compliant	Freedom from holes G1 AQL 0.65
Packaging	One pair per poly wallet, sealed in a poly envelope; 10 pairs per sealed polybag; 5 sealed polybags per master polybag; 4 master polybags per lined carton; 200 pairs per carton.
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin	Sri Lanka
User Needs Segment	Controlled Environment Glove - Gloves that meet the special requirements of cleanroom and aseptic controlled environments.

PHYSICAL PROPERTIES:

PROPERTY	TYPICAL VALUES							TESTING METHOD
	6.0	6.5	7.0	7.5	8.0	8.5	9.0	
SIZE	6.0	6.5	7.0	7.5	8.0	8.5	9.0	ASTM D3767/EN 420
Length (mm)	310	310	310	310	310	310	310	
Average Palm Width (mm)	75	85	90	95	100	110	115	
Freedom from Holes (Inspection level I)	0.65 AQL							ASTM D5151/EN 374-2
Palm Thickness Single Wall	0.15 - 0.21 mm / 5.90 - 8.27 mils							ASTM D3767/EN 420
Particle Count	< 3500 Particle / cm ²							IEST-RP-CC005.4
Endotoxin	< 20 EU / pair							ASTM D7102
	BEFORE AGING			AFTER AGING				
Tensile Strength (MPa)	≥17			≥12				ASTM D 412-06a
Elongation at Break (%)	650			490				ASTM D 412-06a
Force at break (N)	≥9			≥9				EN 455-2

ORDERING INFORMATION:

SIZE	6.0	6.5	7.0	7.5	8.0	8.5	9.0
ASPEN	73711060	73711065	73711070	73711075	73711080	73711085	73711090

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

*Warning: No glove provides complete protection against all chemicals. Users must test the gloves against the particular chemicals and environment in which they will be used.

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa
Ansell Healthcare Europe NV
Riverside Business Park
Blvd International, 55
1070 Brussels, Belgium
+32 2 528 74 00
+32 2 528 74 01

Asia Pacific
Ansell Global Trading Center
(Malaysia) Sdn Bhd
Prima 6, Prima Avenue
Block 3512, Jalan Teknokrat 6
63000 Cyberjaya
Selangor, Malaysia
T: +60 3 83106688
F: +60 3 8318 6699

North America
Ansell Healthcare Products LLC
111 Wood Avenue South
Suite 210
Iselin, NJ 08830, USA
+1 800 800 0444
+1 800 800 0445

Latin America & Caribbean
Ansell Brazil Ltda.
Rua das Figueiras 474 - 4º Andar
Bairro Jardim
SP 09080-300 Santo André
Brazil
CNPJ: 03.496.778/0001-21
+55 11 3356 3100

Australia
Ansell Limited
Level 3, 678 Victoria Street,
Richmond, Vic, 3121
Australia
+61 1800 337 041
+61 1800 803 578

Russia
Анселл РУС
123610 Россия, Москва
Краснопресненская
Наб. 12, п.3, оф. 1304А
Тел. +7 495 258 13 16

Regulatory Compliance



TP TC 019/2011



Performance Standards

