

## Safety / Spectacles / 5X7

## 5X7 - Clear

Code: 5X7.01.00.00

Date: 21-06-22 1/2

5X7 is designed for a perfect integration with prescription glasses. The exclusive SoftPad technology, a high-strength insert combined with rod adjustments, ensure maximum stability even in extreme conditions.



## Frame mark (EU)

Mod.5X7 U EN166 FT U EN175 FT CE

## Lens mark (EU)

2C-1.2 U 1 FT K CE

## Conditions of use

Standard brightness, Low brightness

## Lens color

Clear

## Frame technology

Overspec, Adjustment of temples in length, Rubber Terminal, Terminal tilting movement, SoftPad

## Lens technology

Anti-Scratch (K), UV400

## Lens material

Polycarbonate

## Standards

EN166, EN170

## Scale number

(2C-1.2)

## Mechanical resistance

Low energy impact (F)

## Optical class

Optical class (1)


## Optional requirements

Resistance to surface damage by fine particles (K), Protection against high speed particles at extreme temperatures -5°/+55° C (T)

## Weight

37g

>> <https://www.univetsafety.com/en/products/safety/spectacles/5x7/5x7-clear/>



01.

**UPPER FRONTAL**

Grants comfort and stability with a shockproof effect

02.

**SIDE SHIELDS**

Improved peripheral protection even in combination with eyeglasses

03.

**NO TEMPLES OVERLAPPING**

Avoids the annoying overlapping of temples between the two glasses, for comfort and greater stability even in prolonged use

04.

**RUBBER TERMINAL WITH TILTING MOVEMENT & LENGTH ADJUSTMENT**

Allows to obtain the correct fit and work in constant safety

Attention! Any images on this page illustrate the frame technologies of the product family in question and may represent frame and lens colours that do not correspond to the product code of the following sheet.

**HEADQUARTERS**

Univet S.r.l. Via Giovanni Prati 87 25086 Rezzato - Telephone 030 2499411 - Fax 030 2499430 - [info@univetsafety.com](mailto:info@univetsafety.com)  
VAT. IT02506570163